

型式((HAU-BW/CW)		150	180	240	300	400
-		EXA	EXA	EXA	EXA	EXA
					300	400
					EXSA	EXSA
冷房能力	USRT	150	180	240	300	400
	kW	527	633	844	1,055	1,407

■ 冷水15~7°C/冷却水32~37°C/蒸気圧0.78MPa(G) [冷水大温度差仕様]

(蒸気消費率 EXA:3.5~3.53kg/h・RT、EXSA:3.83kg/h・RT)

型式((HAU-BW/CW)		450	500	560	600	700	800	900	1000
-		EXA	EXA	EXA	EXA	EXA	EXA	EXWA	EXWA
		450	500	560	600	700	800	900	1000
		EXSA	EXSA	EXSA	EXSA	EXSA	EXSA	EXWSA	EXWSA
冷房能力	USRT	450	500	560	600	700	800	900	1,000
	kW	1,582	1,758	1,969	2,110	2,461	2,813	3,165	3,516

型式((HAU-BW/CW)		150	180	240	300	400
-		EX	EX	EX	EX	EX
					300	400
					EXS	EXS
冷房能力	USRT	150	180	240	300	400
	kW	527	633	844	1,055	1,407

■ 冷水12~7°C/冷却水32~37°C/蒸気圧0.78MPa(G) [冷水大温度差仕様]

(蒸気消費率 EX:3.6~3.63kg/h・RT、EXS:3.93kg/h・RT)

型式((HAU-BW/CW)		450	500	560	600	700	800	900	1000
-		EX	EX	EX	EX	EX	EX	EXW	EXW
		450	500	560	600	700	800	900	1000
		EXS	EXS	EXS	EXS	EXS	EXS	EXWS	EXWS
冷房能力	USRT	450	500	560	600	700	800	900	1,000
	kW	1,582	1,758	1,969	2,110	2,461	2,813	3,165	3,516